

ESSENTIALSERIES

DUAL HINGED DOOR

An Advanced Door for a Variety of Applications

Ensure Containment Integrity with Smooth Operation

The Essential Series Dual Hinged Door is a exceptional solution for cold and hot aisle containment solutions. The door is designed so that each door can be opened independently – there is no fixed door. The no-threshold design eliminates any tripping hazard and allows for easy movement of carts in and out of the aisle. The door is designed air-tight thereby protecting the integrity of the enclosure.

KEY FEATURES

- Standard Sizes
- Smooth Actuation
- Rigid Design
- Self Supporting
- Clear Panels
- No Threshold
- Soft Closing

PRODUCT OPTIONS

Clear or Black Finish





DUAL HINGED DOOR

Product Specifications + Drawings

Frame

Physical Properties

| Property | Material |
|------------------|----------|
| Tensile Strength | Aluminum |

| Result |
|------------|
| 22,000 psi |

Shipping

Physical Properties

| Property | Result |
|------------|--------------------|
| Weight | 250 lbs. Approx |
| Components | 4 Major Components |

Standard Size

| Width | Н |
|-------|----|
| 54" | 92 |

.


leight

92.75" 47"





ØT H ß



CONTACT US



Want More? Upgrade to ESSENTIAL PLUS+

+ ENGINEERED

+ UPGRADED MATERIALS

+ EXTENDED LIFETIME WARRANTY

+ WHITE GLOVE

Insert Panels – Options

3mm - Acrylic Flammability

| Property | Test | Result |
|-----------------|-----------|-------------|
| Smoke Dev. | ASTM E84 | 385 |
| Flame Spread | ASTM E84 | 140 |
| Horizontal Burn | ASTM D635 | 1.18 in/min |
| UL Horizontal | UL94 | 94 HB |

4mm — Twin Wall Polycarbonate Flammability

| Property | Test | Result |
|--------------|----------|--------|
| Smoke Dev. | ASTM E84 | 40 |
| Flame Spread | ASTM E84 | 5 |