

ESSENTIALSERIES

DUAL SLIDING DOOR

An Advanced Door for a Variety of Applications

Feature Rich Door with a Low Profile

The Essential Series Dual Sliding Door boasts a sleek, feature-rich, low profile design. The doors slide on an easy-glide track system, allowing for smooth operation and the self-aligning doors require no adjustment. The easy-glide track system and self-closing cartridge are integrated into the doors so that they are tucked away from view when the doors are closed or open. The self-closing cartridge converts from manual to self-closing in minutes and be adjusted for speed. Implement the Essential Series Dual Sliding Door when space is an issue in your data center.

KEY FEATURES

- Standard Sizes
- Smooth Actuation
- Rigid Design
- Self Supporting
- Clear Panels
- Auto Door Closer
- No Threshold
- Soft Closing

PRODUCT OPTIONS

• Clear or Black Finish





DUAL SLIDING DOOR

Product Specifications + Drawings

Frame

Physical Properties

| Property | Material |
|------------------|----------|
| Tensile Strength | Aluminum |

| Result | |
|--------|------------|
| | 22,000 psi |

Shipping

Physical Properties

| Property | Result |
|------------|--------------------|
| Weight | 175 lbs. Approx |
| Components | 7 Major Components |

Standard Size

| Width | Height | |
|-------|--------|--|
| 54" | 92.75" | |

ght 42"

Effective Opening


Insert Panels – Options

3mm - Acrylic Flammability


| Property | Test | Result |
|--------------|---------------|---------------|
| Smoke Dev. | ASTM E84 | 385 |
| Flame Sprea | ad ASTM E84 | 140 |
| Horizontal B | Burn ASTM D63 | 5 1.18 in/min |
| UL Horizont | al UL94 | 94 HB |


4mm — Twin Wall Polycarbonate Flammability

| Property | Test | Result |
|--------------|----------|--------|
| Smoke Dev. | ASTM E84 | 40 |
| Flame Spread | ASTM E84 | 5 |









CONTACT US



Want More? Upgrade to ESSENTIAL PLUS+

+ ENGINEERED

+ UPGRADED MATERIALS

+ EXTENDED LIFETIME WARRANTY

+ WHITE GLOVE